ULTRA-THIN COB LED POSTER SCREEN

Slim die-cast aluminum COB display powered by Android OS. Operates as a standalone unit, or seamlessly splices horizontally with multiple screens. Delivers soft, uniform visuals and multi-channel publishing. Ideal for indoor commercial applications.



Available Pixel Pitch: P1.25mm / P1.56mm

COB Protection

Ultra-thin cabinet

Magnetic Seamless Cascading

Remote Update

HD Display

Front maintenance

ULTRA-THIN CABINET UPRIGHT STD / FOLD OPT

Standard model: upright can foldable foldable version is optional. Folds into compact size for easy transport and handling, perfect for frequent relocation or limited shipping space.



standard：upright



optional：foldable

COB INTEGRATED PACKAGING MODULE


COB integrated packaging creates a flat module surface with no protruding LEDs. Impact-resistant and scratch-proof, dust proof & moisture-proof for reduced failure rate. It delivers consistent, delicate color for stable, superior visual performance.



Module Size: 150 × 168.75mm



High-density LEDs



Hand-link Integrated Plug



Magnetic Positioning

MAGNETIC SEAMLESS CASCADING FREELY EXPANDABLE

Magnetic connection enables flat, frameless splicing of multiple screens to build seamless large-size displays with consistent color. Supports standalone use or multi-screen expansion—flexible and efficient.



Single screen standalone display



Multi-screen horizontal Seamless Splicing (Combines for Large Screen)

FREE ZONING FULL FORMAT COMPATIBILITY

Supports custom screen partition layout. Import multi-format media files with one click and freely add playlist playback effects for diverse commercial display content.

SMART RELEASE CENTRALIZED MANAGEMENT

Multiple input options: Ethernet, USB, HDMI, LAN cluster management. Supports remote program push and batch device control, update content remotely with no on-site operation required.

MAGNETIC FRONT MAINTENANCE

Magnetic hard-link modules adopt direct hard-interface connection (no flat ribbon cables) for stable anti-vibration performance. Front-access disassembly & maintenance is supported; magnetic quick-fit design enables fast on-site servicing.

HIGH DEFINITION DELICATE IMAGE QUALITY

Featuring COB display technology, it delivers delicate images, high refresh rate, high contrast ratio and 160° wide viewing angle for smooth, vivid and consistent visuals. Supports split-screen playback for flexible commercial deployment.

3840Hz
High Refresh Rate

> 7000:1
High Contrast Ratio

160°Wide Angle
No off-color at any angle

PRECISION ENGINEERING

This unit is built to rigorous standards with robust cabinet construction and practical interfaces, ensuring reliable performance, easy installation and maintenance—ideal for diverse commercial display needs.

Practical Interfaces
Easy access, hassle-free playback

Magnetic Connector
Magnetic alignment, fast splicing

Magnetic Frame Strip
Easy assembly & disassembly

Universal Casters
Rotate casters for easy moving

Folding Hinge
Foldable for easy storage & transport

Slim Alu. Cabinet
Ultra-slim, lightweight, easy installation

Reinforced Rear Rib
Anti-deform, stable splice

DIVERSE COMMERCIAL APPLICATION SCENARIOS

Ideal for shopping malls, brand boutiques, hotel lobbies and exhibition halls. Perfect for promotions, brand showcasing and visitor information guidance.

MULTI-ANGLE PRODUCT VIEW

Product Specifications

Product Name	Ultra-thin COB Hard-link LED Poster	
Module Size	150×168.75mm	
Display Size	65"	
Pixel Pitch (mm)	P1.25mm	P1.56 mm
Resolution	480×1520	384×1216
Display Panel Type	COB	
Display Dimension (mm)	W600mm×H2025mm	
Unit Dimension (mm)	W653mm×H2225mm×D82.40mm	
Cabinet Material	Ultra-thin Die-cast Aluminum	
Maintenance	Front Maintenance	
Folding Structure	Optional	
Installation Method	Mobile Floor-standing (Standard) Mobile Foldable (Optional)	
Unit Weight	50kg	
Viewing Angle	160° (H) / 160° (V)	
Brightness (after Vibration)	1000nit, multi-level adjustable	
Contrast Ratio	>7000:1	
Refresh Rate (Hz)	3840Hz	
Operating System	Android 11	
Power Supply	AC100-240V	
Speaker	Optional	
Interfaces	Ethernet, HDMI, USB, Aviation Power	